

COMFORT

Optimising comfort and ensuring the health of occupants Reduce your deployment, integration and operational costs



DEPLOY MORE SIMPLY AND QUICKLY

- Worldwide cellular compatibility (NB-IoT, LTE-M).
- Multi-platform integration facilitated by LWM2M and MQTT standards.
- Automated provisioning on the IoT platform through bootstrapping (LwM2M).
- Mobile application for on-site application configuration in NFC.

MEASURE AND ALERT ACCORDING TO YOUR NEEDS

- Monitor temperature and humidity in a configurable measurement interval from 1 min to 7 days.
- Trigger an alarm in real time thanks to configurable high and/or low thresholds.
- Choose its transmission mode(s): periodic, event-based, with history, black out.

OPERATE YOUR FLEET OVER THE LONG TERM WITH THE LWM2M

- Standardized and remote device management operations, individually or in batches: commands, configuration read/write, FOTA.



MADE IN FRANCE



- **Network:** excellent indoor coverage
- **Quick and easy application configuration,** with a smartphone or remotely
- **Battery-operated product**
- **Historization and blackout:** optimized autonomy
- **Compact design,** easy to install
- **Designed and assembled in France**



Reduce energy consumption



Guarantee occupant satisfaction



Meet to regulatory obligations



Preserve the building against damage

TECHNICAL SPECIFICATIONS



NB-IOT ARF8394AAA

Mechanical specifications

Weight	140 g (battery included)
Dimensions	111 x 61 x 40 mm
Enclosure	IP20, Bayblend® FR3010 (PC/ABS) plastic, white
Mounting	Wall or laid flat

Operating conditions

Range of use recommended	5°C / +50°C
Operating temperature	-10°C / +70°C
Humidity	0 to 85% HR (non-condensing)

Device Power Supply

Battery	Dual FANSO Li-SOCI2 ER18505H-2 battery pack or external power supply via 2-pin terminal block (power supply not supplied)
Expected Battery Life	Up to 15 years without maintenance (device configuration : 1 sampling every 60 mins, 1 transmission every 60 mins).

Update

Applicative configuration	Setup via NFC, using the Adeunis mobile application: "IoT Configurator NB-IoT / LTE-M" on Android/iOS, or remotely.
Firmware	Application firmware and remote modem firmware upgrade (FOTA)

Connectivity

SIM card	Nano SIM 4FF Class C (1.8V)	
Cellular standard	3GPP LTE Version 13	
LPWAN networks	NB-IoT, LTE-Cat-M1	
Protocols	LWM2M 1.1, MQTT (optional)	

Features	NB-IoT	LTE-Cat-M1
Frequency bands	B1, B2, B3, B4, B5, B8, B12, B13, B17, B19, B20, B25, B26, B28, B66	B1, B2, B3, B4, B5, B8, B12, B13, B14, B18, B19, B20, B25, B26, B28, B66
RF transmitting power	+23 dBm	+23 dBm
Sensibility	>-108 dBm -113 dBm typ	>-103 dBm -107 dBm typ

Regulations and certifications

Standard	Directive 2014/53/UE (RED)
----------	----------------------------

SENSORS	Technology	Measuring range	Accuracy
Environmental parameters			
Temperature	CMOSens®	0°C / +65°C	± 0.2°C typ. ± 1°C max.
Humidity	CMOSens®	10% to 90% HR	± 2% HR typ. ± 4.5% HR max

